











Flash Streamer

Powerful air purification

- > Effectiveness against respiratory viruses evaluated by Institute Pasteur de Lille*
- Pure air thanks to Daikin 'Catch and Clean' approach in decomposing harmful substance
- > High performance HEPA filter with no need to change for 10 years
- One of the most silent Air Purifier range on the European market

^{*}Daikin device MCSSWVM (commercial names MCSSW/VB), tested by Institut Pasteur de Lille, removes 99.93 % of Influenza A virus subtype H1N1 in 2.5 minutes running time at 'turbo' speed in laboratory conditions (airtight chamber with inner volume 0.47 m³, no air renewal).

MC55W




MC55W

Indoor Unit				MC	55W
Application					Floor standing type
Applicable room area m ²				m²	41 (1) / 82 (2)
CADR				m³/h	320
Weight	Unit			kg	6.8
Dimensions				mm	598 / 330 / 330
Casing	Colour				White
Fan	Туре				Multi Blade Fan (Sirocco fan)
	Air flow	Air purifying	Silent/Low/	m³/h	66 /120 /192 /330
	rate	operation	Medium/Turbo		
Sound pressure	Air purifying	Silent/Lo	w/Medium/Turbo	dBA	19 /29 /39 /53
level	operation				
Air purifying	Power	Silent/L/	M/Turbo	kW	0.008 /0.010 /0.015 /0.037
operation	input				
Deodorizing method					Flash streamer + Deodorizing catalyst
Dust collecting method					Electrostatic HEPA filter
Air filter	Type				Polyethylene terephthalate net
Sign	Item	01			Dust: 3 stages / Odour: 3 stages / Anti-pollen mode / Child proof lock lamp / PM 2. 5 sensor lamp: 6
					stages / Econo mode / ON/OFF lamp / Streamer lamp / Airflow rate: Quiet/Low/Standard/Turbo / AUTO
					FAN mode
Power supply	Phase/Frequency/Voltage Hz/V			Hz/V	1~/50/60/220-240/220-230
Туре	pe				Air Purifier

(I) The applicable room area is appropriate for operating the unit of maximum fan speed (HH). Applicable room area indicates the space where a certain amount of dust particles can be remover in 30 minutes. (JEM 1467) | (2) Converted to NRCC standards from test values in accordance with JEM1467. | Operating sound levels are the average of values measured at Im away from the front, left, right and top of the unit. (These are equal to the values in an anechoic chamber) | Electrostatic HEPA filter is attached in the unit. | Other function: Active plasmation function. Auto-restart function.

 $\textbf{Daikin Europe} \ \text{Namloze Vennootschap} \cdot \text{Zandvoordestraat 300} \cdot 8400 \ \text{Oostende} \cdot \text{Belgium} \cdot \text{https://www.daikin.eu} \cdot \cdot \cdot \cdot \text{RPR Oostende (Responsible Editor)}$



ECPEN22-702 03/2022

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

